

Maryland Catchment Basin and Containment Sump Test Report

MDE Facility I.D. #:			
Facility Name:	UST Owner:		
Facility Address:	Owner Address:		
City: State: MD Zip:	City: State: Zip:		
	Owner Telephone Number:		
Testing Company:			
Company Telephone Number:			

Product:					
Testing:	√ Check One	√ Check One	√ Check One		
	Spill Bucket	Spill Bucket	Spill Bucket		
	Stage I Bucket	Stage I Bucket	Stage I Bucket		
	Dispenser Sump	Dispenser Sump	Dispenser Sump		
	#	#	#		
	STP Sump	STP Sump	STP Sump		
	Tank Top Sump	Tank Top Sump	Tank Top Sump		
	Transition Sump	Transition Sump	Transition Sump		
	Vent Riser Sump	Vent Riser Sump	Vent Riser Sump		
	Other (Describe):	Other (Describe):	Other (Describe):		
Construction:	Single-walled	Single-walled	Single-walled		
	Double-walled (vacuum	Double-walled (vacuum	Double-walled (vacuum		
	test method must be	test method must be	test method must be		
	performed in accordance	performed in accordance	performed in accordance		
	with manufacturer or PEI/	with manufacturer or PEI/	with manufacturer or PEI/		
	RP1200)	RP1200)	RP1200)		
Start Level:					
Start Time:					
End Level:					
End Time:					
Level Change:		-			
Test Results:	Pass Fail	Pass Fail	Pass Fail		
Test Failure:	Reported to MDE Date: Time:				

⁻ Hydrostatic and vacuum test failures must be reported to MDE immediately and within 2 hours of the test.

March 2017 Page 1 of 2

⁻ A liquid level drop of 1/8 inch or greater in 1 hour is considered a test failure.

Product:				
Testing:	√ Check One	√ Check One	√ Check One	
	Spill Bucket	Spill Bucket	Spill Bucket	
	Stage I Bucket	Stage I Bucket	Stage I Bucket	
	Dispenser Sump	Dispenser Sump	Dispenser Sump	
	#	#	#	
	STP Sump	STP Sump	STP Sump	
	Tank Top Sump	Tank Top Sump	Tank Top Sump	
	Transition Sump	Transition Sump	Transition Sump	
	Vent Riser Sump	Vent Riser Sump	Vent Riser Sump	
	Other (Describe):	Other (Describe):	Other (Describe):	
Construction:	Single-walled	Single-walled	Single-walled	
	Double-walled (vacuum	Double-walled (vacuum	Double-walled (vacuum	
	test method must be	test method must be	test method must be	
	performed in accordance	performed in accordance	performed in accordance	
	with manufacturer or PEI/	with manufacturer or PEI/	with manufacturer or PEI/	
	RP1200)	RP1200)	RP1200)	
Start Level:				
Start Time:				
End Level:				
End Time:				
Level Change:				
Test Result:	Pass Fail	Pass Fail	Pass Fail	
Test Failure	Reported to MDE Date	e: Time: _		
TT 1 4 4*	1 4 4 6 9 4	he was autod to MDE immed		

⁻ Hydrostatic and vacuum test failures must be reported to MDE immediately and within 2 hours of the test.

Tester	Cer	tifica	tion	(check	one).
I CSLCI	CL	шиса	LIVII	CHECK	OHE .

MDE Technician	MDIC-	-	- 1		
MDE Inspector	MDIC-	-	- I		
Precision Tester: Test Method _				Certification Expiration Date:	
Tester's Name (print):			Tester's Signature:		
_				-	

Comments:

Copy of the test report must be maintained by the owner/operator for a period of 5 years and made available to the Department upon request and during UST inspections.

⁻ A liquid level drop of 1/8 inch or greater in 1 hour is considered a test failure.