Technical Memorandum

Nonpoint Sources of Sediment in the Non-Tidal West River Watershed

The U.S. Environmental Protection Agency (USEPA) requires that Total Maximum Daily Load (TMDL) allocations account for all sources of each impairing pollutant (CFR 2012). This technical memorandum identifies the nonpoint sources of sediment in the West River watershed. Detailed allocations are provided for those nonpoint sources included within the West River Sediment TMDL Load Allocations (LAs). These are conceptual values that are designed to meet the TMDL thresholds. The State reserves the right to allocate the sediment TMDL among different sources in any manner that is reasonably calculated to protect the designated uses of the non-tidal West River from sediment related impacts.

The non-tidal West River Sediment TMDL is presented in terms of an average annual load established to ensure the support of aquatic life. Since there are no specific numeric criteria in Maryland that quantify the impact of sediment on the aquatic life of non-tidal stream systems, a reference watershed approach will be used to establish the TMDL. In order to use a reference watershed approach for this TMDL, sediment loads are estimated using a watershed model. For this analysis, the Chesapeake Bay Program Phase 5.3.2 (CBP P5.3.2) watershed model was chosen. The nonpoint source sediment loads generated within the West River watershed are calculated as edge-of-stream (EOS) loads and represent a long-term average loading rate.

Individual land-use EOS baseline loads are calculated as a product of the land-use acreage and the average annual simulated sediment loading rates (ton/ac/yr) from the 2009 Progress Scenario (USEPA 2010). The 2009 Scenario represents 2009 land-use, loading rates, and best management practice (BMP) implementation simulated using precipitation and other meteorological inputs from the period 1991 - 2000 to represent variable hydrological conditions. The 1991 - 2000 simulation period represents the baseline loading rates in the TMDL for Chesapeake Bay segments. Further details of the nonpoint source sediment load calculations can be found in Sections 2.2, 4.2, and 4.3 of the main TMDL report.

Individual LAs for each nonpoint land-use sector were calculated using the allocation methodology in the MD Phase I Watershed Implementation Plan (WIP), which was designed to be equitable, effective, and consistent with water quality standards (MDE 2010). The allocations were calculated by applying equal reductions to the *reducible* loads of all predominant land use sectors. The *reducible* load is defined as the difference between the No Action (NA) scenario and the "Everything, Everyone, Everywhere" (E3) scenario. The NA scenario represents current land-uses without any sediment controls applied, while the E3 scenario represents an application of all possible BMPs and control technologies to current land-use. For more detailed information regarding the calculation of the LA, please see *Maryland's Phase I Watershed Implementation Plan for the Chesapeake Bay Total Maximum Daily Load*.

In the West River watershed, cropland and urban land were identified as the only land uses requiring reductions. Other land uses that individually contributed less than 2% of the total load

West River Sediment TMDL NPS Technical Memorandum Document version: January 2019

FINAL

were not reduced as they would produce no discernible reductions. Forest is not assigned reductions, as it represents the most natural condition in the watershed. Sediment loads from urban lands in this watershed are regulated under the National Pollutant Discharge Elimination System (NPDES) and are considered a point source that must be included in the Waste Load Allocation (WLA) portion of a TMDL (USEPA 2002). Therefore, the reductions required from urban land sediment loads are defined in the point source technical memorandum.

Table 1 provides one possible scenario for the allocations of the nonpoint source sediment loads that will allow the total TMDL to be met in the West River watershed.

Table 1: West River Watershed Sediment TMDL Allocation by Nonpoint Source Category

General Land Use	Detailed Land-Use	Baseline Load (ton/yr)	TMDL (ton/yr)	Reduction (%)
	Forest	141	141	0
Forest	Harvested Forest	10	10	0
AFOs	Animal Feeding Operations	1	1	0
Pasture	Pasture	17	17	0
Crop	Crop	470	425	10
Nursery	Nursery	2	2	0
Total		641	596	7

¹The source categories represent aggregates of multiple sources (e.g., crop is an aggregate of conventional till, conservation till, and hay).

REFERENCES

CFR (Code of Federal Regulations). 2012. 40 CFR 130.2(i). http://edocket.access.gpo.gov/cfr_2011/julqtr/40cfr130.2.htm (Accessed April, 2012).

MDE (Maryland Department of the Environment). 2010. *Maryland's Phase I Watershed Implementation Plan for the Chesapeake Bay Total Maximum Daily Load*. Baltimore, MD: Maryland Department of the Environment. Also available at: http://www.mde.state.md.us/programs/Water/TMDL/Documents/www.mde.state.md.us/assets/document/MD_Phase_I_Plan_12_03_2010_Submitted_Final.pdf

USEPA (U.S. Environmental Protection Agency). 2002. Establishing Total Maximum Daily Load (TMDL) Wasteload Allocations (WLAs) for Storm Water Sources and NPDES Permit Requirements Based on Those WLAs. Washington, DC: U.S. Environmental Protection Agency.

______. 2010. Chesapeake Bay Phase 5.3 Phase 5.3 Community Watershed Model. EPA 903S10002 - CBP/TRS-303-10. U.S. Environmental Protection Agency, Chesapeake Bay Program Office, Annapolis MD. December 2010. Also available at http://ches.communitymodeling.org/models/CBPhase5/documentation.php#p5modeldoc.